



DESCRIPTION

Non-Halogen Cable for 1500V Photovoltaic Power System Class 5 TC Stranding Low Smoke Density, Termite Resisting and Direct Burial Applied.

STANDARDS

IEC 60228, IEC 60332-1-2, IEC 60754, IEC 60811, IEC 61034, IEC 62930
EN 50618
ROHS 2011/65/EU

CABLE CONSTRUCTION



Conductor	Stranded Tinned Copper
Size	6mm ²
Stranding	78/0.30
Diameter	3.0mm
Insulation	XLPO
Minimum Average Thickness	0.7mm
Color	White
Jacket	XLPO
Minimum Average Thickness	0.8mm
Color	Black
Diameter	6.0±0.2mm

ELECTRICAL CHARACTERISTICS (at +20°C)

Voltage Rating	
EN 50618	AC:1000V; DC:Max.1500V
IEC62930	AC:1000V; DC:Max.1500V
Insulation Resistance	≥ 1000 MΩ.km
Voltage Withstand	6500 VAC
Conductor DC Resistance	≤ 3.39 Ω/km

OTHER CHARACTERISTICS

Bending Radius	
Dynamic	≥ 5 X OD
Static	≥ 4 X OD
Flammability	IEC 60332-1-2
Working Temperature	-40°C~+90°C
Cable Light Transmittance	≥ 60%
Termite Test	Termite Resisting

PRINT LEGEND

AKATSUKI H1Z2Z2-K 6mm² TRPV R 50385976 AKATSUKI 62930 IEC 131 6mm² HALOGEN FREE LOW SMOKE R 50406787
—— AKATSUKI H1Z2Z2-K 6mm² TRPV R 50385976 ——— AKATSUKI 62930 IEC 131 6mm² HALOGEN FREE LOW SMOKE R
50406787 ———

Notes: With or without line on whole length above will be required.
Both marking will be required according to the purchase order.

HISTORY

Feb 22, 2018	First issue	Draft
May 7, 2018	Add IEC marking according to IEC 62930 standard requirement	V0